



**Add value.
Inspire trust.**

TÜV SÜD Industrie Service GmbH · Gottlieb-Daimler-Str. 7 · 70794 Filderstadt · Germany

OMARLIFT S.R.L
Mr. Marco Selogni
Via F.lli. Kennedy 22/D
24060 Bagnatica (BG)
Italy

Your reference/letter of	Our reference/name	Tel. extension/Email	Fax extension	Date	Page
	IS-FTT-STG/Be Armin Becker	+49 711 7005-713 armin.becker@tuvsud.com		2026-10-12 SW_Omarlift_HDU35_50_261012.docx	1 of 2

Confirmation letter about a discrepancy in the nominal pressure specification for the hydraulic valve, type HDU 35

Dear Mr. Selogni,

We refer to your email inquiry dated October 2, 2026, regarding a discrepancy in the nominal pressure specification for your hydraulic valve, type HDU 35.

Our company has subjected the hydraulic valve for a brake element as part of a protection means against unintended downward car movement, type HDU 35, to several type examinations and the following certificates have been issued.

Type Examination Certificate No. / EU-Type Examination Certificate No.	Date of issue
ESHV 022	2014-07-28
EU-UCM 022	2016-04-20
EU-UCM 022/1	2021-02-05

You informed us that, during the transition to the Lifts Directive 2014/33/EU (EU-UCM 022), the pressure range for the valve type mentioned above was specified as 10–45 bar within the scope of application. This does not correspond to the originally tested pressure range of 10–50 bar.

Headquarters: Munich
Trade Register Munich HRB 96869
VAT ID No. DE129484218
Information pursuant to § 2 [1] DL-InfoV
(Germany) at tuvsud.com/imprint

Supervisory Board:
Walter Reithmaier (Chairman)
Board of Management:
Simon Kellerer (CEO)
Paula Pias Peleteiro
Markus Starflinger

TÜV SÜD Industrie Service GmbH
Business Area Lifts and Cranes
Department New Technologies
Gottlieb-Daimler-Str. 7
70794 Filderstadt
Germany
Phone: +49 711 7005-765

tuvsud.com/de-is
Hotline: +49 89 5190-4001





After reviewing our records, we can confirm that the scope of application is corrected as follows:

Hydraulic valve for a brake element as part of a protection means against unintended downward car movement, type HDU 35 STAND ALONE and INTEGRATED

Flow, pressure, viscosity, ambient temperature

Range of flow	[l/min]	8 – 55
Range of pressure	[bar]	10 – 50
Range of viscosity	[cSt]	25 – 400
Range of ambient temperature	[° C]	0 – 65

The remaining requirements and conditions remain unchanged.

This document does not replace the above-mentioned EU-type examination certificates but may be attached to them for information purposes.

The amendment will be incorporated into the next revision of the above-mentioned EU-type examination certificate.

For further questions we are gladly at your disposal.

With kind regards

Notified Body LCC

A blue ink signature of Achim Janocha, consisting of a stylized 'A' followed by a horizontal line and a small flourish.

Achim Janocha

Expert

A blue ink signature of Armin Becker, consisting of a stylized 'A' followed by a horizontal line and a small flourish.

Armin Becker